





Performance curves



Overall dimension

Model	L
RTL0.75PM	576
RTL1PM	
RTL1.5PM	
RTL2PM	595
RTL2.5PM	
RTL3PM	
RTL4PM	636



Technical parameter list

Model	Qmax (l/min)	Hmax (m)	Curves	V/Hz	Power(P1)		(Amps)	Fitting size (mm)	G.W (Kg)	Packing size (mm)
					kW	HP				
RTL0.75PM	280	12	1	380V/50Hz	0.55	0.75	3.2	48.5 or 50 60.3 or 63	14	615×300×440
RTL1PM	310	15.5	2	380V/50Hz	0.75	1.0	3.8		14.8	615×300×440
RTL1.5PM	400	18	3	380V/50Hz	1.1	1.5	5.2		15.9	615×300×440
RTL2PM	470	19	4	380V/50Hz	1.5	2.0	7.0		19	635×300×440
RTL2.5PM	520	19.5	5	380V/50Hz	1.85	2.5	8.6		20.2	635×300×440
RTL3PM	550	22	6	380V/50Hz	2.2	3.0	10		20.8	635×300×440
RTL4PM	600	24	7	380V/50Hz	3.0	4.0	14		25	675×300×440

230V/60Hz, 110V/60Hz, 110V/50Hz models are available on request

Working conditions

Medium temperature:

5-50°C

Environmental temperature:

≤50°C

Max. working pressure:

0.7MPa

